GlobeSurfer® III+



3G+ Broadband Access Your Carry-on High Speed Internet & Network

- > Powerful WiFi Network router
- > Plug 'n Play & highly portable
- >Ultra reliable and secure
- > Large easy read front panel with simple 2-button control
- > Smart design: Desktop or wall-mounted
- > Built-in security and firewall functionality
- > File & print server





GlobeSurfer® III+



Updated and optimized, the GlobeSurfer® III+ is the next generation of mobile broadband router. Building on the trusted and proven platform that is the GlobeSurfer® III+ it incorporates the latest Option GTM661 module giving a great boost in performance and efficiency. Its new simple to understand front panel display is for optimal placement of the GlobeSurfer® III+ for best reception whilst ensuring that key status changes are not missed.

Naturally, it comes with full telephone functionality, including composing, reading and managing SMS text messages. Having excellent compatibility with telephone standards you can attach an ordinary telephone and get complete management of calls with functions such as call-hold, divert and Caller Line Identification. For convenience new SMS and calls missed will be flagged on the front panel display.

File and Printer sharing is easy. Connected to the USB port centralised hard drives and printers make it simple for users to back-up or share files and conveniently print documents. Music and movies can be streamed across the network.

The GlobeSurfer® III+ is ideal for the family home but it is also an excellent business router with a full suite of security tools and support for ADSL failover for continuity of connection.

The GlobeSurfer® III+ is also easy to use, with just two buttons and a simple to understand front panel. Its web user interface has been split into two sections; the main section for users who require basic features such as SMS, Telephone, Quick Set-Up and Security, the other section is for the IT administrator who needs the sophisticated and advanced functions.









As part of the continual product improvement process, Option® reserves the right to alter the specifications of this product. Copyright ©2011 OPTION. All rights reserved. Option, GlobeSurfer and the Option logo are registered trademarks of Option. All third-party trademarks are the property of the respective owners.

Specifications

3G (WCDMA)

- > Quad band: 850/900/1900/2100 Mhz
- > Receiver Diversity on all bands
- > HSDPA 14.4 Mbps (Category 10)
- > HSUPA 5.76 Mbps (Category 16)
- > UE Power Class 3 (+24 dBm)

E-GPRS

- > 850/900/1800/1900 MHz
- > GSM Power Class 4 (2W) for 850/900 bands
- > GSM Power Class 1 (1W) for 1800/1900 bands
- > EDGE Class E2 (+27 dBm in 850/900 bands, +26 dBm in 1800/1900 bands)
- > GPRS/EDGE Multislot Class 12
- > GPRS/EDGE Class B Type 1 MT

USE

> Support for external HDDs or USB printers

LAN Interfaces

IEEE 802.11b/g WLAN Access Point

- > WEP, WPA, WPA2
- > 802.11b/g
- > MAC address blocking
- > Possible to disable WLAN radio

Etherne

> 10/100Mbps Auto MDX - 2 ports

Voice Support (UMTS and GSM)

- > RJ11 POTS port
- > AMR, FR, HFR voice codecs
- > Caller ID on telephone display
- > DTMF signal pass through

LAN services

- > DHCP server and proxy
- > DNS server and proxy

VPN functionality

- > VPN pass through
- > PPTP and IPSec client and server
- > L2TP client
- > GRE
- > PPP0E
- > etc.

Firewall and Gateway features

- > Advanced NAT
- > MAC address filtering
- > Demilitarised Zone (DMZ)
- > DoS and intrusion protection
- > Stateful Packet Inspection
- > Configurable security policies
- > Application Level Gateway (ALG) modules
- > Event logging
- > DHCP and DNS server and proxy
- > Dyn DNS
- > Time

Additional specifications

- > Larger clear LED display showing device status, WiFi and Network status, SMS and missed calls indicator.
- > External antenna connector
- > Remote management through SNMP v1, 2 & 3 and Command Line Interface (CLI)
- > Intuitive web-based wizard-driven configuration
- > External 110-240V power adapter
- > Dimensions: 155 x 120 x 27 mm
- > Weight: 255 grams plus power adapter
- > Desktop Form Factor and Wall mountable
- > Operating environment for indoor use: 0°C to +45°C, 5 – 95% humidity

Approvals & Certifications

> All applicable regulatory approvals, Operator and Infrastructure IOT

> CE including automotive 2004/104/EC