



## GSM Desktop Phone

### DPH101

Teltonika DPH101 GSM Desktop Phone allows users to make voice calls in any location covered by a GSM Network. GSM Desktop Phone is intended for use where wired communications infrastructure is not available or not possible. The appliance fully emulates standard landline phone. It also implements advanced call services features making it suitable for office use: call forwarding, call barring, call waiting. Large LCD screen allows for clear reading of text messages and menu navigation. Simple and intuitive control menu helps user to quickly and easily configure advanced phone features. DTMF signaling allows user to use essential operator supplementary services such as voicemail, phone-banking, bill payment or any similar services which require entering digits through the phone keypad.



#### Features:

- Dual Band 900/1800 MHz GSM network
- Full emulation of fixed phone
- Large LCD display
- Speed dial 1-9 numbers
- Perfect sound quality
- User-friendly menu navigation
- SMS Send and Receive



## Specifications

### Display

Operator name  
Time  
Date  
GSM signal strength  
LCD screen dimensions 61x32 mm  
Number of characters per line 20  
Number of lines 6

### Keyboard

Alphabetical standard keypad  
Hotkeys: 4 (send SMS, read SMS, address book, missed calls)  
Additional keys: Cancel, Menu, Names, SMS, Dial

### Sound and tone features

Busy tone  
Dial tone at off hook  
Ringer tone  
10 Ring tones  
16 SMS tones  
Ring tone volume adjustment  
SMS tone volume adjustment  
Speech volume adjustment  
SMS Receive Alert  
Key tone volume on / off

### Network Dependent Features

Call Forwarding  
Call Barring  
Call Waiting  
Calling line presentation restriction  
Calling line identification presentation

### Dialing

Speed Dialing (9 numbers)  
One touch last number dialing

### Memory

Address book 240 entries (SIM dependant)  
SMS memory 30 (SIM dependant)  
Call memory: 10 last dialed, 10 last received, 10 last missed

### Dimensions / weight

Approx. 215 x 170 x 65 mm  
Weight: Approx. 850 g

### Power supply

Mains adaptor: 100 - 240 V AC / 5 V DC  
Power consumption when talking 2W (peak)  
Power Consumption stand by (300mW)

### Temperature and humidity

Operation 0° to 55° C  
Storage temperature -20° to 80° C  
Humidity 10% to 90%  
Storage humidity 5% to 95%

### Other

External omni directional antenna (SMA)  
Antenna Gain 2dBi  
Port for firmware update

**BUY ONLINE IN THE UK FROM WESTLAKE COMMUNICATIONS LTD BY VISITING THE FOLLOWING ONLINE STORES**

[www.discountphonesystems.co.uk](http://www.discountphonesystems.co.uk) or [www.westlake.co.uk](http://www.westlake.co.uk)